



**ProLume** Dimmable



**Energy Efficient**

- Maximum light distribution achieved through compact design
- Save up to 80% in energy costs compared to Incandescent lamps
- Tri-phosphor coating enhances lumen efficacy and color rendering, 82 CRI

**Technical Data**

- Dimmable on analog dimmers
- Electronic Instant Start Ballast
- 120 volt, 60Hz
- -10°F Minimum Starting Temperature
- Nickel-plated brass base

**Broad Assortment**

- Mini-T3, PAR30, R30 and R40
- 13, 15, 18 and 23 watt

**Long Life**

- 8,000-10,000 Hours average rated life

**Benefits**

- Saves energy
- Low maintenance

- » Save energy
- » Low maintenance
- » Compact design

**Markets:**

- Residential
- Commercial

**Applications:**

- Table lamps
- Down lighting
- Ceiling fixtures

where there's light, there's halco®

Contact your account representative at 800.677.3334 for pricing, orders and technical support.

Visit us at [halcolighting.com](http://halcolighting.com)



## Ordering Information

Bulb Type	Watt	Base	Product #	Product Code	Description	Color Temp.	CRI	Initial Lumens	Avg. Rated Life	Pkg. Qty.	MOL	Incandescent Equivalent
<b>SPIRALS</b>												
T3	13 Watt	GU24	46544	CFL13/27/GU24/DIM	Warm White Dimmable	2700	82	800	10000	1/6	4.00"	60
T3	15 Watt	Med.	46330	CFL15/27/DIM	Warm White Dimmable	2700	82	900	10000	1/6	4.92"	60
T3	18 Watt	GU24	46546	CFL18/27/GU24/DIM	Warm White Dimmable	2700	82	1200	10000	1/6	4.40"	75
T3	23 Watt	Med.	46334	CFL23/27/DIM	Warm White Dimmable	2700	82	1600	10000	1/6	5.59"	100
T3	23 Watt	GU24	46548	CFL23/27/GU24/DIM	Warm White Dimmable	2700	82	1600	10000	1/6	4.73"	100
<b>REFLECTORS</b>												
PAR30	15 Watt	Med.	46550	CFL15/27/PAR30/DIM	Warm White Dimmable Flood	2700	82	700	10000	6/24	4.60"	65
R30	15 Watt	Med.	46328	CFL15/27/R30/DIM	Warm White Dimmable Flood	2700	82	680	8000	6/24	6.01"	65
R40	23 Watt	Med.	46329	CFL23/27/R40/DIM	Warm White Dimmable Flood	2700	82	1090	10000	6/24	6.97"	100

**(Hg)** Hg-LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.  
 Visit [www.lamprecycle.org](http://www.lamprecycle.org) for disposal information for your state or local government.

**CAUTION:** This device is not intended for use with emergency exit fixtures. Dimmable lamps may not be compatible with all dimmers. This device complies with Part 18 of the FCC Rules. This product may cause interference with radio equipment and should not be installed near maritime safety communications equipment, ships at sea or other critical navigation or communications equipment operating between 0.45-30 MHz.  
**WARRANTY - Commercial/Industrial:** This product is warranted for 2 years from the date of purchase, based on 3 hours of use per day.