



ProLume.
 < GU24 Spirals

ProLume® GU24 Spirals

Energy Efficient

- Maximum light distribution achieved through compact design
- Save up to 80% in energy costs compared to incandescent lamps
- Tri-phosphor coating enhances lumen efficacy and color rendering

Technical Data

- GU24 base
- Electronic instant start ballast
- End-of-Life protection
- 120 volt, 60Hz
- Minimum starting temperature 5°F
- Nickel-plated brass pins

Broad Assortment

- 11, 13, 15, 18, 23 and 26 watt
- 2700, 3500, 4100, 5000K
- T2, T3, A19, G25, R20 and R30 bulb types

Long Life

- 10,000 Hours Average Rated Life

Benefits

- Use of GU24 socket guarantees use of an energy efficient product
- Saves energy
- Low maintenance

Applications

- Table lamps
- Ceiling fixtures
- Down lighting

Halco
 LIGHTING TECHNOLOGIES

Available in 11,
 13, 15, 18, 23 and
 26 watts.

Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at halcolighting.com.

Your account representative is your single source for pricing, orders and technical support.

Shipping from Atlanta, Cleveland, Houston and Phoenix.

ISO 9001 Certified



**where there's light,
 there's halco®**

(800) 677-3334

halcolighting.com



Bulb Type	Watts	Base	Item #	Product Code	Description	Pkg. Qty.	Color Temp	CRI	Intital Lumens	Incandescent Equivalent	Avg. Rated Life	MOL (Inches)
⊕ R20	11	GU24	46542	CFL11/27/R20/GU24	Warm White	6/24	2700	82	340	50	10000	3.80"
T2	13	GU24	*46506	CFL13/27/GU24	Warm White	10/50	2700	82	800	60	10000	3.63"
⊕ T2	13	GU24	*46525	CFL13/35/GU24	White	10/50	3500	82	800	60	10000	3.63"
T2	13	GU24	*46526	CFL13/41/GU24	Cool White	10/50	4100	82	800	60	10000	3.63"
T2	13	GU24	*46527	CFL13/50/GU24	Natural White	10/50	5000	82	800	60	10000	3.63"
⊕ T3	13	GU24	46544	CFL13/27/GU24/DIM	Warm White Dimmable	10/50	2700	82	800	60	10000	4.00"
⊕ A19	15	GU24	46540	CFL15/27/A19/GU24	Warm White	6/24	2700	82	800	60	10000	4.80"
G25	15	GU24	46536	CFL15/27/G25/GU24	Warm White	6/24	2700	82	750	60	10000	4.80"
R30	15	GU24	46538	CFL15/27/R30/GU24	Warm White	6/24	2700	82	750	65	10000	4.76"
T2	18	GU24	*46512	CFL18/27/GU24	Warm White	10/50	2700	82	1200	75	10000	3.90"
⊕ T2	18	GU24	*46519	CFL18/35/GU24	White	10/50	3500	82	1200	75	10000	3.90"
T2	18	GU24	*46520	CFL18/41/GU24	Cool White	10/50	4100	82	1200	75	10000	3.90"
T2	18	GU24	*46521	CFL18/50/GU24	Natural White	10/50	5000	82	1200	75	10000	3.90"
⊕ T3	18	GU24	46546	CFL18/27/GU24/DIM	Warm White Dimmable	10/50	2700	82	1100	75	10000	4.40"
T2	23	GU24	*46518	CFL23/27/GU24	Warm White	10/50	2700	82	1600	100	10000	4.30"
⊕ T2	23	GU24	*46522	CFL23/35/GU24	White	10/50	3500	82	1600	100	10000	4.30"
T2	23	GU24	*46523	CFL23/41/GU24	Cool White	10/50	4100	82	1600	100	10000	4.30"
T2	23	GU24	*46524	CFL23/50/GU24	Natural White	10/50	5000	82	1600	100	10000	4.30"
⊕ T3	23	GU24	46548	CFL23/27/GU24/DIM	Warm White Dimmable	10/50	2700	82	1600	100	10000	4.85"
T3	26	GU24	*46528	CFL26/27/GU24	Warm White	10/50	2700	82	1750	100	10000	5.20"
⊕ T3	26	GU24	*46531	CFL26/35/GU24	White	10/50	3500	82	1750	100	10000	5.20"
T3	26	GU24	*46529	CFL26/41/GU24	Cool White	10/50	4100	82	1750	100	10000	5.20"
T3	26	GU24	*46530	CFL26/50/GU24	Natural White	10/50	5000	82	1750	100	10000	5.20"

⊕ NEW ITEM!

* UL approved for totally enclosed fixtures with a max ballast case temperature of 90°C for GU24 base lamps, 75°C for medium base lamps.



(Hg) Hg-LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.

Visit www.lamprecycle.org for disposal information for your state or local government.

CAUTION: Should not be used on dimming circuits, timing devices, photo sensors or occupancy sensors.

This device is not intended for use with emergency exit fixtures.

This device complies with Part 18 of the FCC Rules. This product may cause interference with radio equipment and should not be installed near maritime safety communications equipment, ships at sea or other critical navigation or communications equipment operating between 0.45-30 MHz.

WARRANTY - Commercial/Industrial: This product is warranted for 2 years from the date of purchase, based on 10 hours of use per day.