



Bulb Type	Base	Product #	Product Code	Description	Pkg Qty	Color Temp	CRI	Initial Lumens	Incandescent Equivalent	Life	MOL (Inc)	MOD (Inc)
5 Watts												
T2	Cand.	45011	*CFL5/27/E12	Warm White	10/50	2700	82	250	25	10000	3.50"	1.38"
T2	Cand.	45015	*CFL5/35/E12	White	10/50	3500	82	250	25	10000	3.50"	1.38"
T2	Cand.	45017	*CFL5/41/E12	Cool White	10/50	4100	82	250	25	10000	3.50"	1.38"
T2	Cand.	45019	*CFL5/50/E12	Natural White	10/50	5000	82	250	25	10000	3.50"	1.38"
T2	Med.	45010	*CFL5/27	Warm White	10/50	2700	82	250	25	10000	3.56"	1.38"
T2	Med.	46600	CFL5/27/FS	Warm White Full Spiral	10/50	2700	82	300	25	12000	2.98"	1.93"
T2	Med.	45014	*CFL5/35	White	10/50	3500	82	250	25	10000	3.56"	1.38"
T2	Med.	45016	*CFL5/41	Cool White	10/50	4100	82	250	25	10000	3.56"	1.38"
T2	Med.	45018	*CFL5/50	Natural White	10/50	5000	82	250	25	10000	3.56"	1.38"
9 Watts												
T2	Cand.	45031	*CFL9/27/E12	Warm White	10/50	2700	82	500	40	10000	4.00"	1.57"
T2	Cand.	45035	*CFL9/35/E12	White	10/50	3500	82	500	40	10000	4.00"	1.57"
T2	Cand.	45037	*CFL9/41/E12	Cool White	10/50	4100	82	500	40	10000	4.00"	1.57"
T2	Cand.	45039	*CFL9/50/E12	Natural White	10/50	5000	82	500	40	10000	4.00"	1.57"
T2	Med.	45030	*CFL9/27	Warm White	10/50	2700	82	500	40	10000	4.06"	1.57"
T2	Med.	46605	CFL9/27/FS	Warm White Full Spiral	10/50	2700	82	500	40	12000	3.41"	1.93"
T2	Med.	45034	*CFL9/35	White	10/50	3500	82	500	40	10000	4.06"	1.57"
T2	Med.	45036	*CFL9/41	Cool White	10/50	4100	82	500	40	10000	4.06"	1.57"
T2	Med.	45038	*CFL9/50	Natural White	10/50	5000	82	500	40	10000	4.06"	1.57"
11 Watts												
T3	Med.	109240	CFL11/27	Warm White	10/50	2700	82	700	40	12000	4.69"	1.85"
T3	Med.	109242	CFL11/41	Cool White	10/50	4100	82	700	40	12000	4.69"	1.85"
T3	Med.	109244	CFL11/50	Natural White	10/50	5000	82	700	40	12000	4.69"	1.85"
T3	Med.	109224	CFL11/BLU	Blue	10/50	-	-	-	-	8000	4.69"	1.85"
T3	Med.	109226	CFL11/GRN	Green	10/50	-	-	-	-	8000	4.69"	1.85"
T3	Med.	109220	CFL11/RED	Red	10/50	-	-	-	-	8000	4.69"	1.85"
T3	Med.	109222	CFL11/YEL	Yellow	10/50	-	-	-	-	8000	4.69"	1.85"
13 Watts												
T2	Cand.	45051	*CFL13/27/T2/E12	Warm White	10/50	2700	82	900	60	12000	4.19"	1.81"
T2	Cand.	45055	*CFL13/35/T2/E12	White	10/50	3500	82	900	60	12000	4.19"	1.81"
T2	Cand.	45057	*CFL13/41/T2/E12	Cool White	10/50	4100	82	850	60	10000	4.19"	1.81"
T2	Cand.	45059	*CFL13/50/T2/E12	Natural White	10/50	5000	82	850	60	12000	4.19"	1.81"
T2	Med.	45050	*CFL13/27/T2	Warm White	10/50	2700	82	900	60	12000	4.19"	1.81"
T2	Med.	45070	*CFL13/27/T2/4PK	Warm White 4-Pack	20/60	2700	82	900	60	12000	4.19"	1.81"
T2	Med.	46610	CFL13/27/FS	Warm White Full Spiral	10/50	2700	82	840	60	12000	3.84"	1.93"
T2	Med.	45054	*CFL13/35/T2	White	10/50	3500	82	900	60	12000	4.19"	1.81"
T2	Med.	45056	*CFL13/41/T2	Cool White	10/50	4100	82	850	60	10000	4.19"	1.81"
T2	Med.	45073	*CFL13/41/T2/4PK	Cool White 4-Pack	20/60	4100	82	850	60	10000	4.19"	1.81"
T2	Med.	45058	*CFL13/50/T2	Natural White	10/50	5000	82	850	60	10000	4.19"	1.81"
T2	GU24	46506	*CFL13/27/GU24	Warm White GU24	10/50	2700	82	800	60	10000	3.63"	1.81"
⊗ T2	GU24	46525	*CFL13/35/GU24	White GU24	10/50	3500	82	800	60	10000	3.63"	1.81"
T2	GU24	46526	*CFL13/41/GU24	Cool White GU24	10/50	4100	82	800	60	10000	3.63"	1.81"
T2	GU24	46527	*CFL13/50/GU24	Natural White GU24	10/50	5000	82	800	60	10000	3.63"	1.81"
T3	Med.	45101	*CFL13/27	Warm White	10/50	2700	82	850	60	12000	4.44"	1.81"
T3	Med.	45103	*CFL13/35	White	10/50	3500	82	850	60	12000	4.44"	1.81"
T3	Med.	45104	*CFL13/41	Cool White	10/50	4100	82	850	60	12000	4.44"	1.81"
T3	Med.	45105	*CFL13/50	Natural White	10/50	5000	82	850	60	12000	4.44"	1.81"
T3	Med.	45107	*CFL13/65	Daylight	10/50	6500	82	850	60	12000	4.44"	1.81"
⊗ T3	GU24	46544	CFL13/27/GU24/DIM	Warm White Dimmable	10/50	2700	82	800	60	10000	4.00"	1.81"
13/20/25 Watts												
T3	Med.	45720	CFL25/27/3WAY	Warm White 3-Way	10/50	2700	82	900/1200/1600	30/70/100	8000	6.13"	2.36"
T3	Med.	45721	CFL25/41/3WAY	Cool White 3-Way	10/50	4100	82	900/1200/1600	30/70/100	8000	6.13"	2.36"
15 Watts												
T3	Med.	109252	CFL15/27	Warm White	10/50	2700	82	950	60	10000	4.94"	1.85"
T3	Med.	109330	CFL15/35	White	10/50	3500	82	950	60	10000	4.94"	1.85"
T3	Med.	109261	CFL15/41	Cool White	10/50	4100	82	950	60	10000	4.94"	1.85"
T3	Med.	109272	CFL15/50	Natural White	10/50	5000	82	950	60	10000	4.94"	1.85"
T3	Med.	109270	CFL15/BLB	Blacklight-Blue	1/20	-	-	-	60	12000	4.94"	1.85"
T3	Med.	109288	CFL15/YEL	Yellow	1/50	-	-	-	60	12000	4.94"	1.85"
T3	Med.	46330	CFL15/27/DIM	Warm White Dimmable	10/50	2700	82	950	60	10000	5.53"	2.13"
18 Watts												
T2	Med.	45062	*CFL18/27/T2	Warm White	10/50	2700	82	1100	75	10000	4.56"	2.13"
T2	Med.	46615	CFL18/27/FS	Warm White Full Spiral	10/50	2700	82	1280	75	12000	4.33"	2.28"
T2	Med.	45064	*CFL18/35/T2	White	10/50	3500	82	1100	75	10000	4.56"	2.13"
T2	Med.	45065	*CFL18/41/T2	Cool White	10/50	4100	82	1100	75	10000	4.56"	2.13"

Bulb Type	Base	Product #	Product Code	Description	Pkg Qty	Color Temp	CRI	Initial Lumens	Incandescent Equivalent	Life	MOL (Inc)	MOD (Inc)
18 Watts cont'd												
T2	Med.	45066	*CFL18/50/T2	Natural White	10/50	5000	82	1100	75	10000	4.56"	2.13"
T2	GU24	46512	*CFL18/27/GU24	Warm White GU24	10/50	2700	82	1200	75	10000	3.90"	2.13"
T2	GU24	46519	*CFL18/35/GU24	White GU24	10/50	3500	82	1200	75	10000	3.90"	2.13"
T2	GU24	46520	*CFL18/41/GU24	Cool White GU24	10/50	4100	82	1200	75	10000	3.90"	2.13"
T2	GU24	46521	*CFL18/50/GU24	Natural White GU24	10/50	5000	82	1200	75	10000	3.90"	2.13"
T3	Med.	45120	*CFL18/27	Warm White	10/50	2700	82	1200	75	12000	5.31"	2.13"
T3	Med.	45122	*CFL18/35	White	10/50	3500	82	1200	75	12000	5.31"	2.13"
T3	Med.	45123	*CFL18/41	Cool White	10/50	4100	82	1200	75	12000	5.31"	2.13"
T3	Med.	45124	*CFL18/50	Natural White	10/50	5000	82	1200	75	12000	5.31"	2.13"
T3	GU24	46546	CFL18/27/GU24/DIM	Warm White Dimmable	10/50	2700	82	1100	75	10000	4.40"	2.13"
20 Watts												
T3	Med.	109254	CFL20/27	Warm White	10/50	2700	82	1250	75	12000	5.25"	2.13"
T3	Med.	109263	CFL20/41	Cool White	10/50	4100	82	1250	75	12000	5.25"	2.13"
T3	Med.	109274	CFL20/50	Natural White	10/50	5000	82	1250	75	12000	5.25"	2.13"
23 Watts												
T2	Med.	45075	*CFL23/27/T2	Warm White	10/50	2700	82	1600	100	10000	4.92"	2.13"
T2	Med.	46620	CFL23/27/FS	Warm White Full Spiral	10/50	2700	82	1600	100	12000	4.65"	2.28"
T2	Med.	45077	*CFL23/41/T2	Cool White	10/50	4100	82	1600	100	10000	4.92"	2.13"
T2	Med.	45079	*CFL23/50/T2	Natural White	10/50	5000	82	1600	100	10000	4.92"	2.13"
T2	GU24	46518	*CFL23/27/GU24	Warm White GU24	10/50	2700	82	1600	100	10000	4.30"	2.13"
T2	GU24	46522	*CFL23/35/GU24	White GU24	10/50	3500	82	1600	100	10000	4.30"	2.13"
T2	GU24	46523	*CFL23/41/GU24	Cool White GU24	10/50	4100	82	1600	100	10000	4.30"	2.13"
T2	GU24	46524	*CFL23/50/GU24	Natural White GU24	10/50	5000	82	1600	100	10000	4.30"	2.13"
T3	Med.	45250	*CFL23/27	Warm White	10/50	2700	82	1600	100	12000	5.13"	2.13"
T3	Med.	46334	CFL23/27/DIM	Warm White Dimmable	10/50	2700	82	1600	100	10000	5.59"	2.13"
T3	Med.	45252	*CFL23/35	White	10/50	3500	82	1600	100	12000	5.13"	2.13"
T3	Med.	45253	*CFL23/41	Cool White	10/50	4100	82	1600	100	12000	5.13"	2.13"
T3	Med.	45254	*CFL23/50	Natural White	10/50	5000	82	1600	100	12000	5.13"	2.13"
T3	GU24	46548	CFL23/27/GU24/DIM	Warm White Dimmable	10/50	2700	82	1600	100	10000	4.85"	2.13"
26 Watts												
T3	GU24	46528	*CFL26/27/GU24	Warm White GU24	10/50	2700	82	1750	100	10000	5.20"	2.13"
T3	GU24	46531	*CFL26/35/GU24	White GU24	10/50	3500	82	1750	100	10000	5.20"	2.13"
T3	GU24	46529	*CFL26/41/GU24	Cool White GU24	10/50	4100	82	1750	100	10000	5.20"	2.13"
T3	GU24	46530	*CFL26/50/GU24	Natural White GU24	10/50	5000	82	1750	100	10000	5.20"	2.13"
27 Watts												
T3	Med.	109310	CFL27/27	Warm White	10/50	2700	82	1900	100	10000	5.44"	2.44"
T3	Med.	45255	CFL27/35	White	10/50	3500	82	1850	100	10000	5.44"	2.44"
T3	Med.	109312	CFL27/41	Cool White	10/50	4100	82	1850	100	10000	5.44"	2.44"
T3	Med.	109314	CFL27/50	Natural White	10/50	5000	82	1750	100	10000	5.44"	2.44"
32 Watts												
T3	Med.	109316	CFL32/27	Warm White	10/50	2700	82	2250	125	8000	5.56"	2.76"
T3	Med.	109318	CFL32/41	Cool White	10/50	4100	82	2200	125	8000	5.56"	2.76"
T3	Med.	109306	CFL32/50	Natural White	10/50	5000	82	2200	125	8000	5.56"	2.76"
42 Watts												
T3	Med.	109328	CFL42/27	Warm White	6/24	2700	82	2900	150	12000	7.06"	2.83"
T3	Med.	109336	CFL42/41	Cool White	6/24	4100	82	2800	150	12000	7.06"	2.83"
T3	Med.	109338	CFL42/50	Natural White	6/24	5000	82	2800	150	12000	7.06"	2.83"
65 Watts												
T5	Med.	45600	CFL65/27	Warm White	1/6	2700	82	4300	300	10000	9.50"	3.54"
T5	Med.	45604	CFL65/50	Natural White	1/6	5000	82	4300	300	10000	9.50"	3.54"
85 Watts												
T5	Med.	45606	CFL85/27	Warm White	1/6	2700	82	5700	400	10000	10.00"	4.02"
T5	Med.	45610	CFL85/50	Natural White	1/6	5000	82	5700	400	10000	10.00"	4.02"
T5	Med.	45500	CFL85/50/E39	Natural White	1/6	5000	82	5700	400	10000	10.50"	4.02"
105 Watts												
T5	Med.	45618	CFL105/50	Natural White	1/6	5000	82	7000	500	10000	10.75"	4.02"
T5	Med.	45502	CFL105/50/277V	Natural White 277V	1/6	5000	82	7000	500	10000	10.75"	4.02"
T5	Mog.	45614	CFL105/50/E39	Natural White	1/6	5000	82	7000	500	10000	11.25"	4.02"
T5	Mog.	45504	CFL105/50/E39/277V	Natural White 277V	1/6	5000	82	7000	500	10000	11.25"	4.02"

NEW ITEM!

 Represents bulbs that are Energy Star approved.

* UL approved for totally enclosed fixtures with a max ballast case temperature of 90°C for GU24 base lamps, 75°C for medium base lamps.

 Hg-Lamp Contains Mercury, Manage In Accord With Disposal Laws.

Non-dimmable lamps should not be used on dimming circuits, timing devices, photo sensors or occupancy sensors. | This device is not intended for use with emergency exit fixtures. Dimmable lamps may not be compatible with all dimmers.