

# ProLED Panel Family



## ProLED Select Backlit Panel

## ProLED EdgeLit Panel

## ProLED Select Edgelit Panel

Sizes	1x4	2x2	2x4	1x4	2x2	2x4	1x4	2x2	2x4
Wattage	30	30	50	40	30	50	30/35/40 Selectable	30/35/40 Selectable	30/35/45 Selectable
Lumens	3000	3000	5000	4000	3000	5000	3300-5000	3300-5000	3500-5500
LPW	100	100	100	100	100	100	Up to 125	Up to 125	Up to 122
Weight	4.98	4.85	9.03	7.1	6.6	12.1	7.1	6.6	12.1
CCT	3500K/4000K/5000K Selectable			3500K/4000K/5000K			3500K/4000K/5000K Selectable		
CRI	80			80			80		
Voltage	120-277VAC			120-277VAC			120-277VAC		
Dimmable	Yes (0-10V)			Yes (0-10V)			Yes (0-10V)		
Construction	Aluminium			Steel backplate/PC Frame			Steel backplate/PC Frame		
Finish	White			White			White		
Operating Temperature	-20°C - 40°C			-20°C - 40°C			-20°C - 40°C		
IP Rating	IP66			IP65			IP66		
Rated Life	50,000h			50,000h			50,000h		
Warranty	5 Years			5 Years			5 Years		
Certifications	UL, DLC (Standard)			UL, DLC (Standard)			UL, DLC (Standard)		
Options	None			SMK, Battery Backup (pre-installed)			SMK, Battery Backup (field installed)		