

### Key Benefits & Features

- Wattage and Color (CCT) Selectable
- 0-10V Dimming
- 2ft and 4ft Versions Available
- Multiple Mounting Options L70: 50,000 Hour Rated Life
- Wattage Selectable:
  - 2FT - 15/20/25W, 4FT - 20/30/40W
- Field Selectable Color Temperature: 3500K, 4000K, 5000K
- Efficacy of > 130 Lumens Per Watt
- L70 Lumen Maintenance: 50,000 Hours
- 120-277VAC
- Color Rendering Index (CRI) > 80
- Operating Temperature: -20°C to 40°C
- 5 Year Warranty
- White Steel Housing
- Prismatic Polycarbonate Lens
- Bi-Level Motion Sensor

### Competitive Advantage

The linear architectural wrap (LWA) is a versatile fixture that not only can be used in typical commercial applications, but due to the available 45-degree angle mounting bracket the LWA can be used, and is DLC 5.1 Premium qualified, for use stairway applications. This, along with wattage and color selectability make this an extremely versatile and functional luminaire.



The ProLED Select Linear Architectural Wrap Fixture will be a new addition to our already successful ProLED Linear Wrap family. This fixture features multiple mounting options, a simple 'snap on' lens and a large wiring compartment making installation a breeze. They will be available in 2ft and 4ft housings and are CCT Selectable and Wattage Selectable. This ProLED Select Linear Architectural Wrap provides optimal performance and versatility and is an ideal solution for general ambient lighting in commercial applications.



### Conversation Starters

- Do you need a wrap fixture that can be used in a standard commercial application as well as in a stairway?
- Do you need to reduce your stocking SKUs and increase inventory turnover?
- Is having multiple mounting options important to the success of the project?
- Does having multiple motion sensor options, both internally and externally mounted, helpful to meet your exact application needs?

### FAQs

- What kind of dimming comes standard? The linear architectural wrap (LWA) comes standard with 0-10V dimming for typically commercial dimming applications.
- What mounting options are available? Both a suspension mounting kit and 45-degree angle mounting bracket are available as accessories along with the standard surface mounting cutouts on the back of the fixture.
- What accessories are available? In addition to the suspension mounting kit and 45-degree angle mounting bracket, the architectural wrap fixture can also be used with an emergency battery backup, and two different microwave motion sensors, as well as PIR motion sensor.
- What lengths and wattages are available? Both 2-foot and 4-foot lengths are available with a maximum wattage of 25W (3319 lumen) and 40W (5235 lumen) respectively.
- What color temperatures are available? The linear architectural wrap is a CCT selectable luminaire that comes standard with 3500K, 4000K, and 5000K options which can be selected with a dip switch on the fixture.

## COMPETITIVE ANALYSIS

<b>PROLED SELECT WRAP FIXTURE SERIES</b>	<b>Halco</b>	<b>Sylvania</b>	<b>Maxlite</b>	<b>Eiko</b>	<b>Elite</b>	<b>Portor</b>	<b>Columbia</b>	<b>Topaz</b>
<b>Fixture/Wattage (Selectable)</b>	Halco (2ft) 15W-20W-25W Halco (4ft) 20W-30W-40W	Sylvania (2ft) 16W-20W-24W Sylvania (4ft) 28W-34W-44W	Maxlite (2ft) 20W-25W-30W Maxlite (4ft) 23W-35W-48W	Eiko (2ft) 16W-20W-24W Eiko (4ft) 23W-35W-48W	Elite (4ft) 21W-27W-37W	Portor (4ft) 30W-35W-40W	Columbia (4ft) 25W, 30W, 35W	Non Selectable Wattage Topaz (4ft) 40W Topaz (8ft) 60W
<b>Lumen Output</b>	2ft - 2025lm - 3325lm 4ft - 2700lm - 5320lm	4ft - 2860lm - 5720lm	2ft - 2600lm - 3900lm 4ft - 2990lm - 6240lm	2ft - 2600lm - 3900lm 4ft - 2990lm - 6240lm	4ft - 3000lm - 5000lm	4ft - 4050lm - 5280lm	4ft - 3025lm - 4095lm	2ft - 5600lm 4ft - 8960lm
<b>CCT (Selectable)</b>	3500K, 4000K, 5000K	3500K, 4000K, 5000K	3000K, 4000K, 5000K	3500K, 4000K, 5000K	3500K, 4000K, 5000K	3500K, 4000K, 5000K	3500K, 4000K, 5000K	3500K, 4000K, 5000K
<b>LPW</b>	130LPW	130LPW	130LPW	111LPW	130LPW	130LPW	123LPW	130LPW
<b>CRI</b>	>80	>80	>80	>80	>80	>80	>80	>80
<b>Voltage</b>	120-277VAC	120-277VAC	120-277VAC	120-277VAC	120-277VAC	120-277VAC	120-277VAC	120-277VAC
<b>Dimmable</b>	0-10V	0-10V	0-10V	0-10V	0-10V	0-10V	0-10V	0-10V
<b>Construction</b>								
Housing	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel
Finish	White	White	White	White	White	White	White	White
Lens	Prismatic Polycarbonate	Prismatic Acrylic	Prismatic PMMA	Prismatic Acrylic	Prismatic Acrylic	Polycarbonate	Polystyrene	Polycarbonate
<b>Environment</b>	Damp Location	Damp Location	Damp Location	Damp Location	Damp Location	Damp Location	Damp Location	Damp Location
<b>L70</b>	50,000 hours	50,000 hours	100,000 hours	50,000 hours	50,000 hours	50,000 hours	54,000 hours	50,000 hours
<b>Mounting</b>	Surface Mount - Wall and Ceiling Suspended Mount Linkable	Surface Mount V Hook Linkable	Surface Mount Pendant Linkable	Surface Mount	Surface Mount Suspended Mount Linkable	Surface Mount Suspended Mount Pendant Linkable	Surface Mount	Surface Mount Suspended Mount Linkable
<b>Options</b>	Emergency Battery Back Up Bi-Level Motion Sensor	Emergency Battery Back Up Bi-Level Motion Sensor	Emergency Battery Back Up Bi-Level Motion Sensor		Emergency Battery Back Up Bi-Level Motion Sensor	Emergency Battery Back Up Bi-Level Motion Sensor	Emergency Battery Back Up Bi-Level Motion Sensor	Emergency Battery Back Up Bi-Level Motion Sensor
<b>Warranty</b>	5 Year	5 Year	10 Year	5 Year	5 Year	5 Year	5 Year	5 Year
<b>Certifications / Ratings</b>								
UL	Yes	Yes	Yes	-	Yes	Yes	Yes	Yes
ETL	-	-	-	Yes	-	-	-	-
DLC 5.1	Premium - Stairway Standard - Linear Ambient	Premium	Premium	Standard	Premium	Premium	Premium	Premium