

COMPETITIVE ANALYSIS

ProLED Select SekurPak	<u>Halco</u>	<u>Hubbell</u>	<u>Westgate</u>	<u>Lithonia</u>	<u>Howard</u>	<u>RAB</u>	<u>EIKO</u>
	SekurPak	<u>Perimashield</u>	<u>LESW</u>	<u>TWS</u>	<u>MiniLED</u>	<u>Brisk</u>	<u>Cube</u>
							
Wattages	(15W) SKWP-15-FS-U (20W) SKWP-20-FS-U (26W) SKWP-26-FS-U	22W	15W 20W	18W	20W	9W, 14W 22W, 35W	15W 20W
Lumen Range	1950-3500	2104-2130 lm	1675-2500 lm	2124 lm	1205 lm	1100-4900 lm	1900-2600 lm
LPW	120-148 LPW	92-96 LPW	125 LPW	118 LPW	61 LPW	120-144 LPW	120-130 LPW
CCT Selectability	Yes	No	No	No	No	No	Yes
CCT	3000K/4000K/5000K	4000K & 5000K	3000K & 5000K	5000K	5000K	3000K, 4000K & 5000K	3000K/4000K/5000K
CRI	>80	>70	>80	>80	>85	>80	>70
Voltage	120-277V	120-277V	120-277V	120-277V	120-277V	120-277V	120-277V
Dimming	Non-Dimming	Non-Dimming	Non-Dimming	Non-Dimming	Non-Dimming	0-10V	Non-Dimming
Photocell	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Operating Temperature	-4°F to 113°F	-4°F to 103°F	-4°F to 113°F	-40°F to 104°F	-22°F to 103°F	-22°F to 104°F	-4°F to 113°F
Construction							
Housing	Die-Cast Aluminum & PolyCarb	Die-Cast Aluminum & PolyCarb	Die-Cast Aluminum & PolyCarb	Die-Cast Aluminum & PolyCarb	Die-Cast Aluminum & PolyCarb	Die-Cast Aluminum & PolyCarb	Die-Cast Aluminum & PolyCarb
Finish	Bronze	Bronze	Bronze & White	Bronze	Bronze	Bronze & White	Bronze
Rated Life	>50,000	>50,000	>70,000	>50,000	>50,000	>60,000	>50,000
Warranty	5 Year	5 Year	7 Year	5 Year	5 Year	5 Year	5 Year
Certifications / Ratings							
UL	Yes	Yes	Yes	Yes	Yes	Yes	Yes
DLC 5.0	Standard	No	No	Standard	No	Premium	Standard
IP Rating	IP65	IP65	IP65	IP65	IP65	IP66	IP65