


ProLume. Pulse Start Metal Halide Ballast Specifications


BALLAST SPECIFICATIONS				
Input Volts	120V	208V	240V	277V
Frequency	60Hz			
Circuit Type	CWA			
Input Power	400W			
Starting Current	3.1A	1.6A	1.5A	1.2A
Operating Current	3.3A	1.9A	1.6A	1.4A
Open Circuit Current	1.6A	1.0A	0.8A	0.7A
Recommended Fuse	12A	6A	6A	5A
Open Circuit Volts	257V			
Short Circuit Current (Input)	1.1-3.3A	0.6-1.8A	0.5-1.5A	0.5-1.5A
Short Circuit Current (Secondary)	2.8-4.2A			
Insulation System	Class N, 200°C			
UL 1029 Bench Top Rise Code	A	A	A	A
Min. Starting Temp	-22°F / -30°C			

CAPACITOR




Diameter: 1.88"
Height: 3.75"
Cap.: 24µF
Minimum Volts: 400V
Case Max. Temp.: 90°C

WIRING DIAGRAM




Cap unused leads with wire nuts.

IGNITOR




SOCKETS



Product Number	Product Code	Terminal	Lead Length
91010	SKT/E39/4KV	Screw	10"
91011	SKT/E26/4KV	Screw	18"

BALLAST DIMENSIONS



Dim. (A): 2.32"
Dim. (B): 4.40"
Weight: 11.80 lbs
Lead Length: 12"

Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

PN# 55150

