

ProLED. Elevator Series







High power LED with superior thermal construction for long life and energy efficient illumination



10-18V Range Eliminates Voltage Drop Calculation

R12 with BA15s and BA15d base

5-Year Limited Warranty

Applications:

Education Healthcare Hospitality Office Retail

Markets:

Commercial



where there's light, there's halco®

Contact Your Customer Care Specialist For Pricing, Orders And Technical Support.


800.677.3334 www.halcolighting.com




Product #:	Type:
Project:	Date:
Comments:	Initials:

Specifications

- Provide 20 times the life of traditional Incandescent
- 87% more efficient than a 20W Incandescent¹
- 2700K Color temperature for warm white illumination
- 82 CRI for quality and consistent color rendering



Energy Savings Comparison



^v Maintenance costs based on 15 minutes at \$40 per/hr



Ordering Information

Watt	Base	Product #	Product Code	Volts	Color Temp.	CRI	Lumens	СВСР	Useful Life*	Pkg. Qty.	MOL
2.6	BA15d	80756	GBF/3WW/LED	10-18	2700	82	145	410	40,000	1/10	2.52"
 2.6	BA15s	80701	1383/3WW/LED	10-18	2700	82	145	410	40,000	1/10	2.52"

^{*} Useful Life is defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to burn past this point, but at decreased light levels. Warranty – Commercial / Industrial: This product is warranted for 5 years from the date of purchase, based on 10 hours of use per day.

Not for use in enclosed fixtures.

[¥] Energy costs based on \$0.11 kWh

¹ Energy savings based on \$0.11 kWh over the life of the ProLED lamp.