

ProLume® Bare Spirals Applications

Compact Fluorescent lamps are being specified for a growing number of applications, especially where the objectives are energy savings and reduced maintenance costs. ProLume® CFLs can save up to 80% in energy costs and last up to ten times longer than standard Incandescent lamps. Use the chart below to determine the best lamp for your application.

- = Lamp is acceptable in application
- = Lamp is NOT acceptable in application



Spiral



Spiral GU24

Model	Indoor					Outdoor	
	Open Non-Recessed	Open Recessed	ICAT Recessed	Totally Enclosed Recessed	Enclosed Non-Recessed	Enclosed Non-Recessed	Damp Location
5 Watt							
CFL5/27, CFL5/35, CFL5/41, CFL5/50							
CFL5/27/E12, CFL5/35/E12, CFL5/41/E12, CFL5/50/E12							
CFL5/27/FS							
9 Watt							
CFL9/27, CFL9/35, CFL9/41, CFL9/50							
CFL9/27/E12, CFL9/50/E12							
CFL9/27/FS							
11 Watt							
CFL11/27, CFL11/41, CFL11/50							
13 Watt							
CFL13/27/FS							
CFL13/27/T2, CFL13/35/T2, CFL13/41/T2, CFL13/50/T2, CFL13/65/T2							
CFL13/27/T2/E12, CFL13/35/T2/E12, CFL13/41/T2/E12, CFL13/50/T2/E12							
CFL13/27/GU24, CFL13/35/GU24, CFL13/41/GU24, CFL13/50/GU24							
CFL13/27/GU24/DIM							
15 Watt							
CFL15/27, CFL15/35, CFL15/41, CFL15/50, CFL15/YEL							
CFL15/27/DIM							
CFL15/BLB							
18 Watt							
CFL18/27/T2, CFL18/35/T2, CFL18/41/T2, CFL18/50/T2							
CFL18/27/GU24, CFL18/35/GU24, CFL18/41/GU24, CFL18/50/GU24							
CFL18/27/GU24/DIM							

ProLume® Bare Spirals Applications

Compact Fluorescent lamps are being specified for a growing number of applications, especially where the objectives are energy savings and reduced maintenance costs. ProLume® CFLs can save up to 80% in energy costs and last up to ten times longer than standard Incandescent lamps. Use the chart below to determine the best lamp for your application.

- = Lamp is acceptable in application
- = Lamp is NOT acceptable in application



Spiral



Spiral GU24

Model	Indoor					Outdoor	
	Open Non-Recessed	Open Recessed	ICAT Recessed	Totally Enclosed Recessed	Enclosed Non-Recessed	Enclosed Non-Recessed	Damp Location
20 Watt							
CFL20/27, CFL20/41, CFL20/50	Yellow	Yellow	Yellow	Yellow	Yellow	Yellow	Blue
23 Watt							
CFL23/27/T2, CFL23/35/T2, CFL23/41/T2, CFL23/50/T2	Yellow	Yellow	Yellow	Yellow	Yellow	Yellow	Blue
CFL23/27/DIM	Yellow	Yellow	Blue	Blue	Blue	Blue	Blue
CFL23/27/GU24, CFL23/35/GU24, CFL23/41/GU24, CFL23/50/GU24	Yellow	Yellow	Yellow	Yellow	Yellow	Yellow	Blue
CFL23/27/GU24/DIM	Yellow	Yellow	Yellow	Yellow	Yellow	Yellow	Blue
25 Watt							
CFL25/27/3WAY	Yellow	Yellow	Blue	Blue	Blue	Blue	Blue
26 Watt							
CFL26/27/T2, CFL26/35/T2, CFL26/41/T2, CFL26/50/T2	Yellow	Yellow	Yellow	Yellow	Yellow	Yellow	Blue
CFL26/27/GU24, CFL26/35/GU24, CFL26/41/GU24, CFL26/50/GU24	Yellow	Yellow	Yellow	Yellow	Yellow	Yellow	Blue
32 Watt							
CFL32/27, CFL32/41, CFL32/50	Yellow	Yellow	Blue	Blue	Blue	Blue	Blue
40 Watt							
CFL40/27, CFL40/41, CFL40/50	Yellow	Yellow	Blue	Blue	Blue	Blue	Blue
65 Watt							
CFL65/27, CFL65/50	Yellow	Blue	Blue	Blue	Blue	Blue	Blue
85 Watt							
CFL85/27, CFL85/50, CFL85/50/E39	Yellow	Blue	Blue	Blue	Blue	Blue	Blue
105 Watt							
CFL105/50, CFL105/50/277V, CFL105/50/E39, CFL105/50/E39/277V	Yellow	Blue	Blue	Blue	Blue	Blue	Blue
150 Watt							
CFL150/50/EX39	Yellow	Blue	Blue	Blue	Blue	Blue	Blue
180 Watt							
CFL180/50/EX39	Yellow	Blue	Blue	Blue	Blue	Blue	Blue