

## Exit & Emergency

### Evade Emergency Light Series

- White or Black Thermoplastic Emergency Unit
- Compact, Contemporary Appearance
- Fully Adjustable LED Heads
- Wall or Ceiling Mount
- Remote Capacity Option
- LED Life-Cycle Exceeding 10 Years

### Specifications



### Description

The Evade Emergency Unit Series offers a quality emergency lighting solution along the path of egress for hallway, stairwells, and other Life Safety applications. The compact design makes it ideal to mount on walls or ceilings illuminating the path of egress for a minimum of 90 minutes after a power loss. Available with remote capacity.

### Electrical

- 120 / 277 VAC, 50/60Hz input
- Emergency test button and battery charging indicator
- Long-life maintenance free NiCad battery
- 24 Hour recharge time
- Low voltage battery protection circuit
- Overload/short circuit protection
- (2) Two 1.0W lamp heads delivering 240 lumens
- 5700K CCT
- Optional 1.5W remote capacity

### Construction & Mounting

- White or Black housings
- Rugged, injection molded, flame retardant, high temperature thermoplastic
- Designed for quick installation
- Suitable for wall and ceiling mount
- Universal J-box mounting pattern on back plate

### Certifications

- UL924 Damp Location listed
- NFPA 101 and NFPA 70
- CEC T20 compliant
- 10°C - 40°C operating temperature

# Evade Emergency Light Series

## Ordering Information

Product SKU	Product Code	Product Description
95008	EV-EME-R	Evade Emergency Unit, White Housing
95009	EV-EME-R-RC	Evade Emergency Unit, White Housing with Remote Capacity
96008	EV-EME-R-BK	Evade Emergency Unit, Black Housing
96009	EV-EME-R-BK-RC	Evade Emergency Unit, Black Housing with Remote Capacity
Remote Heads		
95010	EV-RH-1-IND	Evade Single Remote Indoor Round Head, White
97116	EMG-RH-1-IND-BK	Emergence Single Remote Indoor Round Head, Black
95011	EV-RH-2-IND	Evade Double Remote Indoor Round Head, White
97117	EMG-RH-2-IND-BK	Emergence Double Remote Indoor Round Head, Black
97012	EV2-RH-1-OUT-RD	Evade Single Remote Outdoor Round Head, White
97118	EMG-RH-1-OUT-RD-BK	Emergence Single Remote Outdoor Round Head, Black
97013	EV2-RH-2-OUT-RD	Evade Double Remote Outdoor Round Head, White
97119	EMG-RH-2-OUT-RD-BK	Emergence Double Remote Outdoor Round Head, Black

## Specifications Table

	EV-EME-R-xx	EV-EME-R-xx-RC
Input Current	80mA Max	100mA Max
Input Wattage	0.8W	1W
Battery	Ni-Cad	Ni-Cad
Lamp Head Wattage	1W Ea (2W Total)	
Lamp Head Lumens	240 LM	220 LM
Recharge Time	24 Hours	
Input Voltage	120 or 277 VAC	
Remote Capacity	-	1.5W
Output Voltage	-	3.6VDC
Frequency	50/60Hz	
Housing	Injection-Molded Thermoplastic Housing	
Testing Function	Manual Push to Test Button	
Operating Temperature	10°C to 40°C	
Listings & Compliance	UL 924, CEC Title 20, NFPA 70 & NFPA 101	
Environment	Damp Location Listed	
Warranty*	2 Year	

\*All life safety equipment, including emergency lighting for path of egress must be maintained, serviced, and tested in accordance with all National Fire Protection Association (NFPA) and local codes. Failure to perform the required maintenance, service, or testing could jeopardize the safety of occupants and will void all warranties.

Exit and Emergency

## Evade Emergency Light Series

### Remote Head Specifications

Product SKU	Product Code	Input Voltage	Input Wattage	Lumens	Operating Temperature
95010	EV-RH-1-IND	3.6VDC	.8W	85	0°C-50°C
97116	EMG-RH-1-IND-BK	3.6VDC	.8W	85	0°C-50°C
95011	EV-RH-2-IND	3.6VDC	1.5W	170	0°C-50°C
97117	EMG-RH-2-IND-BK	3.6VDC	1.5W	170	0°C-50°C
97012	EV2-RH-1-OUT-RD	3-12VDC	.8W	75	-25°C-50°C
97118	EMG-RH-1-OUT-RD-BK	3-12VDC	.8W	75	-25°C-50°C
97013	EV2-RH-2-OUT-RD	3-12VDC	1.5W	150	-25°C-50°C
97119	EMG-RH-2-OUT-RD-BK	3-12VDC	1.5W	150	-25°C-50°C

### Remote Head



**EV-RH-1-IND**  
**EMG-RH-1-IND-BK**

- Single, white or black, remote indoor head
- Suitable for damp location. UL cUL listed
- Compatible Halco Exits, EM Units and Combos with remote capacity



**EV-RH-2-IND**  
**EMG-RH-2-IND-BK**

- Double, white or black, remote indoor head
- Suitable for damp location. UL, cUL listed
- Compatible Halco Exits, EM Units and Combos with remote capacity



**EV2-RH-1-OUT-RD**  
**EMG-RH-1-OUT-RD-BK**

- Single, white or black, remote outdoor head
- Suitable for wet location. UL, cUL listed
- Compatible Halco Exits, EM Units and Combos with remote capacity



**EV2-RH-2-OUT-RD**  
**EMG-RH-2-OUT-RD-BK**

- Double, white or black, remote outdoor heads
- Suitable for wet location. UL, cUL listed
- Compatible Halco Exits, EM Units and Combos with remote capacity

### Dimensions

