

Par & R Performance, Essential Series

Essential Series

Performance Series

- 80+ CRI
 - White Housings
- Flood
- 90+ CRI
- White and Black Housings
- Narrow Flood and Flood

Higher Efficacy and L70

 Title 20 and Title 24-JA8-2019





Specifications

Description

Halco's PAR and BR/R portfolio offers two distinct series which meet the needs of different users and applications. The "milk, bread, and eggs" of the line is the Essential Series. This series meets the needs of the everyday user with standard 80+ CRI, white housing, and standard flood beam angles. The Performance series is Halco's "filet mignon" boasting 90+ CRI, white and black housings, and both narrow and standard flood beam angles. In addition, the Performance Series provides higher efficacy, L70, and warranty while meeting Title 20 and Title 24-JA8-2019 requirements.

Performance

Essential Series

- Light Efficacy: 77-92
- L70: 25,000 hours
- Color Rendering Index (CRI): 80+
- Available in 2700K, 3000K, 4000K, and 5000K
- Voltage: 120VAC
- Dimming: Triac
- Light Distribution: Flood (PAR: 40 Degrees, R/BR: 110)

Performance Series

- Light Efficacy: 84-108
- L70: 25,000 (BR/R), 40,000 (PAR) Hours
- Color Rendering Index (CRI): 90+
- Available in 2700K, 3000K, 4000K, and 5000K
- Voltage: 120VAC
- Dimming: Triac
- Light Distribution: Flood (PAR: 30 or 40 Degrees, R/BR: 110)

Certifications

- Damp Location Rated (BR/R's)
- Wet Location Rated (PAR)
- UL Listed
- Energy Star Rated
- RoHS Compliant
- Title 20 and Title 24-JA8-2019 Compliant (Performance Series Only)

Construction

Essential Series

- Housing: Plastic, White Only
- Lens: Plastic
 - BR/R: Standard opaque
 - PAR: Concave parabolic

Performance Series

- Housing: Plastic, White and Black
- Lens: Plastic
 - BR/R: Standard opaque
- PAR30/38: Flat parabolic
- PAR20: Concave parabolic

Applications

- General Residential and Commercial Spaces
- Downlighting
- Education
- Healthcare
- Hospitality
- Retail
- Office



DATE:	LOCATION:	
TYPE:	PROJECT:	
CATALOG #:		

Par & R Performance, Essential Series

Product Selector

						Color Ten	nperature						
					2700K	3000K	4000K	5000K					
			Single PK		80290	80291	80292	80293					
	Essentia	1	6РК		80294	80295	USE SIN	IGLE PK					
BR30			Single PK		80278	80279	80280	80281					
	Performan	ice	6PK		USE SINGLE PK								
	Essentia	I	Single PK		80282	80283	80284	80285					
BR40	Performance		Single PK		80286	80287	80288	80289					
	Essentia	I	Single PK		80264	80265	80266	80267					
R20	Performan	ice	Single PK		80268	80269	80270	80271					
			51.0.00	WHITE	80200	80201	80202	80203					
	Essentia	I	FLOOD	BLACK									
			NARROW FLOOD	WHITE		USE PERFORM	MANCE SERIES						
PAR20	20		51.0.00	WHITE	80208	80209	80210	80211					
	Performan	ice	FLOOD	BLACK	80212	80213	80214	80215					
			NARROW FLOOD	WHITE	80204	80205	80206	80207					
				WHITE	80216	80217	80218	80219					
			FLOOD	BLACK									
		Neck	NARROW FLOOD	WHITE		USE PERFORM	RMANCE SERIES						
	Essential			WHITE	80220	80221	80222	80223					
		Long Neck	FLOOD	BLACK									
			NARROW FLOOD	WHITE		USE PERFORM	IANCE SERIES						
PAR30				WHITE	80232	80233	80234	80235					
		Short Neck	FLOOD	BLACK	80228	80229	80230	80231					
	- (NARROW FLOOD	WHITE	80224	80224	80226	80227					
	Performance	Performance	Performance	Performance			WHITE	80244	80245	80246	80247		
		Long Neck	FLOOD	BLACK	80240	80241	80242	80243					
			NARROW FLOOD	WHITE	80236	80237	80238	80239					
			51.0.00	WHITE	80248	80249	80250	80251					
	Essential		FLOOD	BLACK									
			NARROW FLOOD	WHITE		USE PERFORM	IANCE SERIES						
PAR38			FL 0.02	WHITE	80260	80261	80262	80263					
	Performan	ce	FLOOD	BLACK	80256	80257	80258	80259					
			NARROW FLOOD	WHITE	80252	80253	80254	80255					

Page 2/7 Rev Date: 02/21/24 Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612 | Fax 800.880.0822 | halcolighting.com | Atlanta | Chicago | Cleveland | Houston | Phoenix © 2023 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change



DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

Par & R Performance, Essential Series

Ordering Logic Example: 10PAR30L-FL-LED-930-D-BLK-PS

Wattage / Shape	-	Beam Angle	-	Technology	-	CRI	-	Dimmability	-	Housing Color	-	Series	-	Pack
PAR30L = PAR30 Long		FI = Flood		LED		9 = 90+ CRI 30 = 3000K		D = Dimmable		Blank = White Blk = Black		ES = Essential Series PS = Performance Series		Blank = Single Pack 6PK = 6-Pack

Ordering Information

Product SKU	Product Code	Product Description	Watts	Base	Volts	Dimmable	Color Temp	CRI	Lumens	Useful Life	Beam Type	Beam Angle	Warranty
PAR20													
80204	7PAR20-NFL-LED-927-D-PS	6.5WATT LED PAR20 NARROW FLOOD (30D) DIMMING 90+ CRI 2700K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	2700K	90	550	40,000	Narrow Flood	30°	5
80205	7PAR20-NFL-LED-930-D-PS	6.5 WATT LED PAR20 NARROW FLOOD (30D) DIMMING 90+ CRI 3000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	3000К	90	550	40,000	Narrow Flood	30°	5
80206	7PAR20-NFL-LED-940-D-PS	6.5 WATT LED PAR20 NARROW FLOOD (30D) DIMMING 90+ CRI 4000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	4000K	90	550	40,000	Narrow Flood	30°	5
80207	7PAR20-NFL-LED-950-D-PS	6.5 WATT LED PAR20 NARROW FLOOD (30D) DIMMING 90+ CRI 5000K WHITE HOUSING T20 (PERFORMANCE SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	5000K	90	550	40,000	Narrow Flood	30°	5
80208	7PAR20-FL-LED-927-D-PS	6.5 WATT LED PAR20 FLOOD (40D) DIMMING 90+ CRI 2700K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	2700K	90	550	40,000	Flood	40°	5
80209	7PAR20-FL-LED-930-D-PS	6.5 WATT LED PAR20 FLOOD (40D) DIMMING 90+ CRI 3000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	3000К	90	550	40,000	Flood	40°	5
80210	7PAR20-FL-LED-940-D-PS	6.5 WATT LED PAR20 FLOOD (40D) DIMMING 90+ CRI 4000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	4000K	90	550	40,000	Flood	40°	5
80211	7PAR20-FL-LED-950-D-PS	6.5 WATT LED PAR20 FLOOD (40D) DIMMING 90+CRI 5000K WHITE HOUSING T20 (PERFORMANCE SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	5000K	90	550	40,000	Flood	40°	5
80212	7PAR20-FL-LED-927-D-BLK-PS	6.5 WATT LED PAR20 FLOOD (40D) DIMMING 90+ CRI 2700K BLACK HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	2700K	90	550	40,000	Flood	40°	5
80213	7PAR20-FL-LED-930-D-BLK-PS	6.5 WATT LED PAR20 FLOOD (40D) DIMMING 90+ CRI 3000K BLACK HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	3000К	90	550	40,000	Flood	40°	5
80214	7PAR20-FL-LED-940-D-BLK-PS	6.5 WATT LED PAR20 FLOOD (40D) DIMMING 90+ CRI 4000K BLACK HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	4000K	90	550	40,000	Flood	40°	5
80215	7PAR20-FL-LED-950-D-BLK-PS	6.5 WATT LED PAR20 FLOOD (40D) DIMMING 90+ CRI 5000K BLACK HOUSING T20 (PERFORMANCE SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	5000K	90	550	40,000	Flood	40°	5
PAR3C	S												
80224	11PAR30S-NFL-LED-927-D-PS	11 WATT LED PARSOS NARROW FLOOD (30D) DIMMING 90+CRI 2700K WHITE HOUSING T20/T24 JAB-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	2700K	90	1000	40,000	Narrow Flood	30°	5
80225	11PAR30S-NFL-LED-930-D-PS	11 WATT LED PAR3OS NARROW FLOOD (30D) DIMMING 90+ CRI 3000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	3000к	90	1000	40,000	Narrow Flood	30°	5
80226	11PAR30S-NFL-LED-940-D-PS	11 WATT LED PAR3OS NARROW FLOOD (30D) DIMMING 90+ CRI 4000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	4000K	90	1000	40,000	Narrow Flood	30°	5
80227	11PAR30S-NFL-LED-950-D-PS	11 WATT LED PAR3OS NARROW FLOOD (30D) DIMMING 90+ CRI 5000K WHITE HOUSING T20 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	5000K	90	1000	40,000	Narrow Flood	30°	5
80228	11PAR30S-FL-LED-927-D-BLK-PS	11 WATT LED PAR30S FLOOD (40D) DIMMING 90+ CRI 2700K BLACK HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	2700K	90	1000	40,000	Flood	40°	5
80229	11PAR30S-FL-LED-930-D-BLK-PS	11 WATT LED PAR30S FLOOD (40D) DIMMING 90+ CRI 3000K BLACK HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	3000K	90	1000	40,000	Flood	40°	5
80230	11PAR30S-FL-LED-940-D-BLK-PS	11 WATT LED PAR30S FLOOD (40D) DIMMING 90+ CRI 4000K BLACK HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	4000K	90	1000	40,000	Flood	40°	5
80231	11PAR30S-FL-LED-950-D-BLK-PS	11 WATT LED PAR30S FLOOD (40D) DIMMING 90+ CRI 5000K BLACK HOUSING T20 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	5000K	90	1000	40,000	Flood	40°	5
80232	11PAR30S-FL-LED-927-D-PS	11 WATT LED PAR30S FLOOD (40D) DIMMING 90+ CRI 2700K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	2700K	90	1000	40,000	Flood	40°	5
80233	11PAR30S-FL-LED-930-D-PS	11 WATT LED PAR30S FLOOD (40D) DIMMING 90+ CRI 3000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	3000К	90	1000	40,000	Flood	40°	5
80234	11PAR30S-FL-LED-940-D-PS	11 WATT LED PAR30S FLOOD (40D) DIMMING 90+ CRI 4000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	4000K	90	1000	40,000	Flood	40°	5
80235	11PAR30S-FL-LED-950-D-PS	11 WATT LED PAR30S FLOOD (40D) DIMMING 90+ CRI 5000K WHITE HOUSING T20 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	5000K	90	1000	40,000	Flood	40°	5

Page 3/7 Rev Date: 02/21/24 Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612 | Fax 800.880.0822 | halcolighting.com | Atlanta | Chicago | Cleveland | Houston | Phoenix © 2023 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change



Product Code

DATE:	LOCATION:	
TYPE:	PROJECT:	

Color Temp

Dimmable

Volts

Useful Life

CRI Lumens

Beam Type

Beam Angle

Warranty

3 з з з

з з 3

з

з

3

з

з

Product Description

9.5 WATT LED BR30 FLOOD DIMMING 90+ CRI 5000K WHITE HOUSING T20 (PERFORMANCE SERIES)

13 WATT LED BR30 FLOOD DIMMING 90+ CRI 2700K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)

13 WATT LED BR30 FLOOD DIMMING 90+ CRI 3000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)

13 WATT LED BR30 FLOOD DIMMING 90+ CRI 4000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)

13 WATT LED BR30 FLOOD DIMMING 90+ CRI 5000K WHITE HOUSING T20 (PERFORMANCE SERIES)

PSPerformance

LED Lamps

Product SKU

PAR30

80236	11PAR30L-NFL-LED-927-D-PS	11 WATT LED PAR3OL NARROW FLOOD (30D) DIMMING 90+ CRI 2700K WHITE HOUSING T20/T24 JAB-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	2700K	90	1000	40,000	Narrow Flood	30°	
80237	11PAR30L-NFL-LED-930-D-PS	11 WATT LED PAR3OL NARROW FLOOD (30D) DIMMING 90+ CRI 3000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	3000к	90	1000	40,000	Narrow Flood	30°	
80238	11PAR30L-NFL-LED-940-D-PS	11 WATT LED PAR30L NARROW FLOOD (30D) DIMMING 90+ CRI 4000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	4000K	90	1000	40,000	Narrow Flood	30°	
80239	11PAR30L-NFL-LED-950-D-PS	11 WATT LED PAR3OL NARROW FLOOD (30D) DIMMING 90+ CRI 5000K WHITE HOUSING T20 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	5000K	90	1000	40,000	Narrow Flood	30°	
80240	11PAR30L-FL-LED-927-D-BLK-PS	11 WATT LED PAR30L FLOOD (40D) DIMMING 90+ CRI 2700K BLACK HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	2700K	90	1000	40,000	Flood	40°	
80241	11PAR30L-FL-LED-930-D-BLK-PS	11 WATT LED PAR30L FLOOD (40D) DIMMING 90+ CRI 3000K BLACK HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	3000К	90	1000	40,000	Flood	40°	
80242	11PAR30L-FL-LED-940-D-BLK-PS	11 WATT LED PAR30L FLOOD (40D) DIMMING 90+ CRI 4000K BLACK HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	4000K	90	1000	40,000	Flood	40°	
80243	11PAR30L-FL-LED-950-D-BLK-PS	11 WATT LED PAR3OL FLOOD (40D) DIMMING 90+ CRI 5000K BLACK HOUSING T20 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	5000K	90	1000	40,000	Flood	40°	
80244	11PAR30L-FL-LED-927-D-PS	11 WATT LED PAR30L FLOOD (40D) DIMMING 90+ CRI 2700K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	2700K	90	1000	40,000	Flood	40°	
80245	11PAR30L-FL-LED-930-D-PS	11 WATT LED PAR30L FLOOD (40D) DIMMING 90+ CRI 3000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	3000к	90	1000	40,000	Flood	40°	
80246	11PAR30L-FL-LED-940-D-PS	11 WATT LED PAR30L FLOOD (40D) DIMMING 90+ CRI 4000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	4000K	90	1000	40,000	Flood	40°	
80247	11PAR30L-FL-LED-950-D-PS	11 WATT LED PAR3OL FLOOD (40D) DIMMING 90+ CRI 5000K WHITE HOUSING T20 (PERFORMANCE SERIES)	11W	Medium (E26)	120V	Yes - Triac	5000K	90	1000	40,000	Flood	40°	
PAR38	3												
80252	14PAR38-NFL-LED-927-D-PS	14 WATT LED PAR38 NARROW FLOOD (30D) DIMMING 90+ CRI 2700K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	14W	Medium (E26)	120V	Yes - Triac	2700K	90	1250	40,000	Narrow Flood	30°	
80253	14PAR38-NFL-LED-930-D-PS	14 WATT LED PAR38 NARROW FLOOD (30D) DIMMING 90+ CRI 3000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	14W	Medium (E26)	120V	Yes - Triac	3000к	90	1250	40,000	Narrow Flood	30°	
80254	14PAR38-NFL-LED-940-D-PS	14 WATT LED PAR38 NARROW FLOOD (30D) DIMMING 90+ CRI 4000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	14W	Medium (E26)	120V	Yes - Triac	4000K	90	1250	40,000	Narrow Flood	30°	
80255	14PAR38-NFL-LED-950-D-PS	14 WATT LED PAR38 NARROW FLOOD (30D) DIMMING 90+ CRI 5000K WHITE HOUSING T20 (PERFORMANCE SERIES)	14W	Medium (E26)	120V	Yes - Triac	5000K	90	1250	40,000	Narrow Flood	30°	
80256	14PAR38-FL-LED-927-D-BLK-PS	14 WATT LED PAR38 FLOOD (40D) DIMMING 90+ CRI 2700K BLACK HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	14W	Medium (E26)	120V	Yes - Triac	2700К	90	1250	40,000	Flood	40°	[
80257	14PAR38-FL-LED-930-D-BLK-PS	14 WATT LED PAR38 FLOOD (40D) DIMMING 90+ CRI 3000K BLACK HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	14W	Medium (E26)	120V	Yes - Triac	3000к	90	1250	40,000	Flood	40°	
80258	14PAR38-FL-LED-940-D-BLK-PS	14 WATT LED PAR38 FLOOD (40D) DIMMING 90+ CRI 4000K BLACK HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	14W	Medium (E26)	120V	Yes - Triac	4000K	90	1250	40,000	Flood	40°	
80259	14PAR38-FL-LED-950-D-BLK-PS	14 WATT LED PAR38 FLOOD (40D) DIMMING 90+ CRI 5000K BLACK HOUSING T20 (PERFORMANCE SERIES)	14W	Medium (E26)	120V	Yes - Triac	5000K	90	1250	40,000	Flood	40°	
80260	14PAR38-FL-LED-927-D-PS	14 WATT LED PAR38 FLOOD (40D) DIMMING 90+ CRI 2700K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	14W	Medium (E26)	120V	Yes - Triac	2700K	90	1250	40,000	Flood	40°	
80261	14PAR38-FL-LED-930-D-PS	14 WATT LED PAR38 FLOOD (40D) DIMMING 90+ CRI 3000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	14W	Medium (E26)	120V	Yes - Triac	3000К	90	1250	40,000	Flood	40°	
80262	14PAR38-FL-LED-940-D-PS	14 WATT LED PAR38 FLOOD (40D) DIMMING 90+ CRI 4000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	14W	Medium (E26)	120V	Yes - Triac	4000K	90	1250	40,000	Flood	40°	
80263	14PAR38-FL-LED-950-D-PS	14 WATT LED PAR38 FLOOD (40D) DIMMING 90+ CRI 5000K WHITE HOUSING T20 (PERFORMANCE SERIES)	14W	Medium (E26)	120V	Yes - Triac	5000K	90	1250	40,000	Flood	40°	
R20													
80268	6R20-FL-LED-927-D-PS	6 WATT LED R20 FLOOD DIMMING 90+ CRI 2700K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	6W	Medium (E26)	120V	Yes - Triac	2700K	90	550	25,000	Flood	110	
80269	6R20-FL-LED-930-D-PS	6 WATT LED R20 FLOOD DIMMING 90+ CRI 3000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	6W	Medium (E26)	120V	Yes - Triac	3000к	90	550	25,000	Flood	110	
80270	6R20-FL-LED-940-D-PS	6 WATT LED R20 FLOOD DIMMING 90+ CRI 4000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	6W	Medium (E26)	120V	Yes - Triac	4000K	90	550	25,000	Flood	110	
80271	6R20-FL-LED-950-D-PS	6 WATT LED R20 FLOOD DIMMING 90+ CRI 5000K WHITE HOUSING T20 (PERFORMANCE SERIES)	6W	Medium (E26)	120V	Yes - Triac	5000K	90	550	25,000	Flood	110	
BR30													
80278	10BR30-FL-LED-927-D-PS	9.5 WATT LED BR30 FLOOD DIMMING 90+ CRI 2700K WHITE HOUSING T20/T24 JAB-2019 (PERFORMANCE SERIES)	9.5W	Medium (E26)	120V	Yes - Triac	2700K	90	800	25,000	Flood	110°	
80279	10BR30-FL-LED-930-D-PS	9.5 WATT LED BR30 FLOOD DIMMING 90+ CRI 3000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	9.5W	Medium (E26)	120V	Yes - Triac	3000к	90	800	25,000	Flood	110°	
80280	10BR30-FL-LED-940-D-PS	9.5 WATT LED BR30 FLOOD DIMMING 90+ CRI 4000K WHITE HOUSING T20/T24 JA8-2019 (PERFORMANCE SERIES)	9.5W	Medium (E26)	120V	Yes - Triac	4000K	90	800	25,000	Flood	110°	

9.5W

13W

13W

13W

13W

Medium (E26)

Medium (E26)

Medium (E26)

Medium (E26)

Medium (E26)

Yes - Triac

120V

120V

120V

120V

120V

5000K

2700K

3000К

4000K

5000K

90

90

90

90

90

800

1100

1100

1100

1100

25,000

25,000

25,000

25,000

25,000

Flood

Flood

Flood

Flood

Flood

110°

110°

110°

110°

110°

CATALOG #:

Base

Watts

10BR30-FL-LED-950-D-PS

13BR40-FL-LED-927-D-PS

13BR40-FL-LED-930-D-PS

13BR40-FL-LED-940-D-PS

13BR40-FL-LED-950-D-PS

80281

BR40

80286

80287

80288

80289

Page 4/7 Rev Date: 02/21/24 Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612 | Fax 800.880.0822 | halcolighting.com | Atlanta | Chicago | Cleveland | Houston | Phoenix © 2023 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change



LOCATION: DATE: PROJECT: TYPE: CATALOG #:

LED Lamps

Par & R Performance, Essential Series

Specifications Table

	PAR20	PAR30S	PAR30L	PAR38	R20	BR30	BR40					
Nominal Wattage	6.5W	6.5W 11W 11W		14W	6W	9.5W	13W					
Delivered Lumens	550lm	1000lm	1000lm	1250lm	550lm	800lm	1100lm					
сст		2700K, 3000K, 4000K, 5000K										
Efficacy (lm/W)	85	85 91 91 100 92 84 85										
CRI		90+										
L70 Lifetime (hrs)		25,000 - 40,000										
Voltage				120V								
Dimming				Yes - Triac								
Housing Material				Plastic								
Operating Temperature				-20°C - 40°C								
Listings	UL Listed, Energ	y Star, Title 20, Title 2	4-JA2019, RoHS, We	et Location Rated		rgy Star, Title 20, Titl S, Damp Location Ra						
Environment		Wet Locat	tion Rated		C C	Damp Location Rated	l					
Warranty			3 0	r 5 Year (See Above T	able)							



DATE:	LOCATION:
TYPE:	PROJECT:

Par & R Performance, Essential Series

Ordering Information

Product SKU	Product Code	Product Description	Watts	Base	Volts	Dimmable	Color Temp	CRI	Lumens	Useful Life	Beam Type	Beam Angle	Warranty
PAR20													
80200	7PAR20-FL-LED-827-D-ES	6.5 WATT LED PAR20 FLOOD (40D) DIMMING 80+ CRI 2700K WHITE HOUSING (ESSENTIAL SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	2700К	80	550	25,000	Flood	40°	3
80201	7PAR20-FL-LED-830-D-ES	6.5 WATT LED PAR20 FLOOD (40D) DIMMING 80+ CRI 3000K WHITE HOUSING (ESSENTIAL SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	3000К	80	550	25,000	Flood	40°	3
80202	7PAR20-FL-LED-840-D-ES	6.5 WATT LED PAR20 FLOOD (40D) DIMMING 80+ CRI 4000K WHITE HOUSING (ESSENTIAL SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	4000K	80	550	25,000	Flood	40°	3
80203	7PAR20-FL-LED-850-D-ES	6.5 WATT LED PAR20 FLOOD (40D) DIMMING 80+ CRI 5000K WHITE HOUSING (ESSENTIAL SERIES)	6.5W	Medium (E26)	120V	Yes - Triac	5000K	80	550	25,000	Flood	40°	з
PAR30	S												
80216	11PAR30S-FL-LED-827-D-ES	11 WATT LED PAR30S FLOOD (40D) DIMMING 80+ CRI 2700K WHITE HOUSING (ESSENTIAL SERIES)	11W	Medium (E26)	120V	Yes - Triac	2700К	80	850	25,000	Flood	40°	3
80217	11PAR30S-FL-LED-830-D-ES	11 WATT LED PAR3OS FLOOD (40D) DIMMING 80+ CRI 3000K WHITE HOUSING (ESSENTIAL SERIES)	11W	Medium (E26)	120V	Yes - Triac	3000К	80	850	25,000	Flood	40°	з
80218	11PAR30S-FL-LED-840-D-ES	11 WATT LED PAR3OS FLOOD (40D) DIMMING 80+ CRI 4000K WHITE HOUSING (ESSENTIAL SERIES)	11W	Medium (E26)	120V	Yes - Triac	4000К	80	850	25,000	Flood	40°	з
80219	11PAR30S-FL-LED-850-D-ES	11 WATT LED PAR3OS FLOOD (40D) DIMMING 80+ CRI 5000K WHITE HOUSING (ESSENTIAL SERIES)	11W	Medium (E26)	120V	Yes - Triac	5000K	80	850	25,000	Flood	40°	з
PAR30	L												
80220	11PAR30L-FL-LED-827-D-ES	11 WATT LED PAR3OL FLOOD (40D) DIMMING 80+ CRI 2700K WHITE HOUSING (ESSENTIAL SERIES)	11W	Medium (E26)	120V	Yes - Triac	2700K	80	850	25,000	Flood	40°	з
80221	11PAR30L-FL-LED-830-D-ES	11 WATT LED PAR3OL FLOOD (40D) DIMMING 80+ CRI 3000K WHITE HOUSING (ESSENTIAL SERIES)	11W	Medium (E26)	120V	Yes - Triac	3000К	80	850	25,000	Flood	40°	з
80222	11PAR30L-FL-LED-840-D-ES	11 WATT LED PAR3OL FLOOD (40D) DIMMING 80+ CRI 4000K WHITE HOUSING (ESSENTIAL SERIES)	11W	Medium (E26)	120V	Yes - Triac	4000К	80	850	25,000	Flood	40°	3
80223	11PAR30L-FL-LED-850-D-ES	11 WATT LED PAR3OL FLOOD (40D) DIMMING 80+ CRI 5000K WHITE HOUSING (ESSENTIAL SERIES)	11W	Medium (E26)	120V	Yes - Triac	5000K	80	850	25,000	Flood	40°	3
PAR38													
80248	13PAR38-FL-LED-827-D-ES	13 WATT LED PAR38 FLOOD (40D) DIMMING 80+ CRI 2700K WHITE HOUSING (ESSENTIAL SERIES)	13W	Medium (E26)	120V	Yes - Triac	2700К	80	1200	25,000	Flood	40°	3
80249	13PAR38-FL-LED-830-D-ES	13 WATT LED PAR38 FLOOD (40D) DIMMING 80+ CRI 3000K WHITE HOUSING (ESSENTIAL SERIES)	13W	Medium (E26)	120V	Yes - Triac	3000К	80	1200	25,000	Flood	40°	3
80250	13PAR38-FL-LED-840-D-ES	13 WATT LED PAR38 FLOOD (40D) DIMMING 80+ CRI 4000K WHITE HOUSING (ESSENTIAL SERIES	13W	Medium (E26)	120V	Yes - Triac	4000K	80	1200	25,000	Flood	40°	3
80251	13PAR38-FL-LED-850-D-ES	13 WATT LED PAR38 FLOOD (40D) DIMMING 80+ CRI 5000K WHITE HOUSING (ESSENTIAL SERIES)	13W	Medium (E26)	120V	Yes - Triac	5000K	80	1200	25,000	Flood	40°	3
R20													
80264	7R20-FL-LED-827-D-ES	7 WATT LED R20 FLOOD DIMMING 80+ CRI 2700K WHITE HOUSING (ESSENTIAL SERIES)	7W	Medium (E26)	120V	Yes - Triac	2700К	80	500	25,000	Flood	110°	3
80265	7R20-FL-LED-830-D-ES	7 WATT LED R20 FLOOD DIMMING 80+ CRI 3000K WHITE HOUSING (ESSENTIAL SERIES)	7W	Medium (E26)	120V	Yes - Triac	3000К	80	500	25,000	Flood	110°	3
80266	7R20-FL-LED-840-D-ES	7 WATT LED R20 FLOOD DIMMING 80+ CRI 4000K WHITE HOUSING (ESSENTIAL SERIES)	7W	Medium (E26)	120V	Yes - Triac	4000K	80	500	25,000	Flood	110°	3
80267	7R20-FL-LED-850-D-ES	7 WATT LED R20 FLOOD DIMMING 80+ CRI 5000K WHITE HOUSING (ESSENTIAL SERIES)	7W	Medium (E26)	120V	Yes - Triac	5000K	80	500	25,000	Flood	110°	3
BR30													
80290	8BR30-FL-LED-827-DIM-ES	8 WATT LED BR30 FLOOD DIMMING 80+ CRI 2700K WHITE HOUSING (ESSENTIAL SERIES)	8W	Medium (E26)	120V	Yes - Triac	2700К	80	650	25,000	Flood	110°	3
80291	8BR30-FL-LED-830-DIM-ES	8 WATT LED BR30 FLOOD DIMMING 80+ CRI 3000K WHITE HOUSING (ESSENTIAL SERIES)	8W	Medium (E26)	120V	Yes - Triac	3000К	80	650	25,000	Flood	110°	3
80292	8BR30-FL-LED-840-DIM-ES	8 WATT LED BR30 FLOOD DIMMING 80+ CRI 4000K WHITE HOUSING (ESSENTIAL SERIES)	8W	Medium (E26)	120V	Yes - Triac	4000K	80	650	25,000	Flood	110°	3
80293	8BR30-FL-LED-850-DIM-ES	8 WATT LED BR30 FLOOD DIMMING 80+ CRI 5000K WHITE HOUSING (ESSENTIAL SERIES)	8W	Medium (E26)	120V	Yes - Triac	5000K	80	650	25,000	Flood	110°	3
80294	8BR30-FL-LED-827-DIM-ES-6-PK	8 WATT LED BR30 FLOOD DIMMING 80+ CRI 2700K WHITE HOUSING (ESSENTIAL SERIES) - 6PK	8W	Medium (E26)	120V	Yes - Triac	2700К	80	650	25,000	Flood	110°	3
80295	8BR30-FL-LED-830-DIM-ES-6-PK	8 WATT LED BR30 FLOOD DIMMING 80+ CRI 3000K WHITE HOUSING (ESSENTIAL SERIES) - 6PK	8W	Medium (E26)	120V	Yes - Triac	3000К	80	650	25,000	Flood	110°	3
BR40													
80282	13BR40-FL-LED-827-D-ES	13 WATT LED BR40 FLOOD DIMMING 80+ CRI 2700K WHITE HOUSING (ESSENTIAL SERIES)	13W	Medium (E26)	120V	Yes - Triac	2700К	80	1100	25,000	Flood	110°	3
80283	13BR40-FL-LED-830-D-ES	13 WATT LED BR40 FLOOD DIMMING 80+ CRI 3000K WHITE HOUSING (ESSENTIAL SERIES)	13W	Medium (E26)	120V	Yes - Triac	3000К	80	1100	25,000	Flood	110°	3
80284	13BR40-FL-LED-840-D-ES	13 WATT LED BR40 FLOOD DIMMING 80+ CRI 4000K WHITE HOUSING (ESSENTIAL SERIES)	13W	Medium (E26)	120V	Yes - Triac	4000K	80	1100	25,000	Flood	110°	3
80285	13BR40-FL-LED-850-D-ES	13 WATT LED BR40 FLOOD DIMMING 80+ CRI 5000K WHITE HOUSING (ESSENTIAL SERIES)	13W	Medium (E26)	120V	Yes - Triac	5000K	80	1100	25,000	Flood	110°	3

Page 6/7 Rev Date: 02/21/24 Halco Lighting Technologies 2940 Pacific Drive | Norcross, GA 30071 | Toll Free 800.677.3334 | Phone 770.242.3612 | Fax 800.880.0822 | halcolighting.com | Atlanta | Chicago | Cleveland | Houston | Phoenix © 2023 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change



DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

Par & R Performance, Essential Series

Specifications Table

	PAR20	PAR30S	PAR30L	PAR38	R20	BR30	BR40						
Nominal Wattage	6.5W	11W	11W 13W		7W	8W	13W						
Delivered Lumens	550lm	850lm	850lm	1240lm	500lm	650lm	1100lm						
сст		2700K, 3000K, 4000K, 5000K											
Efficacy (Im/W)	85	77	77	95	71	81	85						
CRI		80+											
L70 Lifetime (hrs)		25,000											
Voltage				120V									
Dimming				Yes - Triac									
Housing Material				Plastic									
Operating Temperature				-20°C - 40°C									
Listings	UL	Listed, Energy Star, Ro	oHS, Wet Location Ra	ited	UL Listed, Energ	gy Star, RoHS, Damp I	Location Rated						
Environment		Wet Locat	tion Rated		[C	Damp Location Rated							
Warranty				3 Years									