

Exit & Emergency

Emergence Die-Cast Aluminum LED Exit Sign

- Die-Cast Aluminum LED Exit Sign
- Brushed Aluminum Face with Black Housing
- Field Selectable Red/Green Stencil Face
- Field Selectable Single/Double Face
- Field Selectable AC or Emergency
- Field Selectable Manual Test or Self-Diagnostics

Specifications

Description

Halco's Emergence die-cast aluminum LED exit sign is constructed of high-strength aluminum combining both elegance and performance while maintaining optimal energy efficiency with bright, uniform illumination. The field-selectable red/green stencil face, field-selectable single/double face, and universal ceiling/end/wall mounting includes field-selectable chevron indicators as well as universal input voltage to provide the most field configurable exit sign on the market. Halco's die-cast exit now comes standard with field-selectable AC or Emergency mode as well as field-selectable Manual Test or Self-Diagnostics. The rugged design makes it ideal to mount on ceilings or walls in surface, ceiling or end mount configurations, indicating the path of egress for a minimum of 90 minutes after a power loss.

Electrical

- 120 / 277 VAC, 60Hz input
- Long-life maintenance free LiFePO4 battery
- Battery low voltage circuit protection
- 24 hour recharge time
- Selectable AC or Emergency mode
- Selectable Manual Test or Self-Diagnostics
- 10°C - 40°C operating temperature

Certifications

- UL924 Damp Location listed
- NFPA 101 and NFPA 70
- CEC T20 Compliant

EMERGENCE™ SERIES



Construction & Mounting

- Brushed aluminum face with black housing
- Fully illuminated 6" characters with 3/4" stroke
- Field-selectable, snap in and out chevrons
- Field-selectable Red/Green stencil
- Suitable for wall, ceiling and end mount with canopy included
- Universal J-Box mounting pattern on back plate
- 5 year warranty

Exit & Emergency

Emergency Die-Cast Aluminum LED Exit Sign

Ordering Information

Product SKU	Product Code	Product Description
97112	EMG-DCEX-BABK-RG	Emergency LED Die-Cast Exit Sign, Selectable Red/Green Legend, Brushed Aluminum Face, Black Housing, Single/Double Face, Selectable Manual or Self-Diagnostics, Selectable AC or Battery Back-Up

Specifications Table

	EMG-DCEX-BABK-R
Letter Color	Selectable Red/Green
ELECTABLE	.30mA Max
Battery	LiFePO4
Recharge Time	<24 Hours
Input Voltage	120 or 277 VAC
Frequency	60Hz
Housing	Die-Cast Aluminum
Testing Function	Selectable Manual or Self-Diagnostics
Operating Temperature	10°C to 40°C
Listings & Compliance	UL 924, CEC Title 20, NFPA 70 & NFPA 101
Environment	Damp Location Listed
Warranty*	5 Year

*All life safety equipment, including emergency lighting for path of egress must be maintained, serviced, and tested in accordance with all National Fire Protection Association (NFPA) and local codes. Failure to perform the required maintenance, service, or testing could jeopardize the safety of occupants and will void all warranties.

Dimensions

