

Exit & Emergency

Evade Exit/Emergency Combination Series

- LED Thermoplastic Exit Sign/EM Unit Combo
- Choice of Red or Green Stencil Face
- Remote Capacity Option
- Fully Adjustable LED Heads
- Universal Single / Double Face
- LED Life-Cycle exceeding 10 years

Specifications

Description

The Evade Exit and Emergency Unit Combo Series offers a quality exit and emergency lighting solution for hallway, stairwell, and other Life Safety applications. The low profile design makes it ideal to mount on walls or ceilings indicating and illuminating the path of egress for a minimum of 90 minutes after a power loss. Available with remote capacity.

Electrical

- 120 / 277 VAC, 60Hz input
- Emergency test button and battery charging indicator
- Long-life maintenance free nicad battery
- 24 hour recharge time
- Battery low voltage protection circuit
- Solid state transfer circuit
- 8w lamp heads delivering 150 lumens
- 5700K CCT
- 10°C - 40°C operating temperature

Certifications

- UL924 Damp Location listed
- NFPA 101 and NFPA 70
- CEC T20 compliant



Construction & Mounting

- Rugged, injection-molded, flame retardant, high temperature, white thermoplastic housing
- Fully illuminated 6" characters with 3/4" stroke
- Field-selectable, snap in and out chevrons
- Suitable for wall and ceiling mount
- Universal J-Box mounting pattern on back plate

Evade Exit/Emergency Combination Series

Ordering Information

Product SKU	Product Code	Product Description
95004	EV-EXC-GR	Evade Exit Sign & Emergency Unit Combination with Green Lettering
95005	EV-EXC-RD	Evade Exit Sign & Emergency Unit Combination with Red Lettering
95006	EV-EXC-GR-RC	Evade Exit Sign & Emergency Unit Combination with Green Lettering and Remote Capacity
95007	EV-EXC-RD-RC	Evade Exit Sign & Emergency Unit Combination with Red Lettering and Remote Capacity
Remote Heads		
95010	EV-RH-1-IND	Evade Single Indoor Round Remote Head
95011	EV-RH-2-IND	Evade Double Indoor Round Remote Head
96012	EV-RH-1-OUT	Evade Single Outdoor Round Remote Head
95013	EV-RH-2-OUT	Evade Double Outdoor Round Remote Head

Specifications Table

	EV-EXC-GR	EV-EXE-RD	EV-EXE-GR-RC	EV-EXE-RD-RC
Letter Color	Green	Red	80mA Max	100mA Max
Input	30mA Max		33mA Max	
Wattage	2.8W		3.5W	
Battery	Ni-cad 3.6V900mAh		Ni-cad 3.6V900mAh (2)	
Lamp Head Wattage	.75W Ea (1.5W Total)			
Lamp Head Lumens	150 LM			
Recharge Time	24 Hours			
Input Voltage	120 or 277 VAC			
Output Voltage	3.6V DC			
Frequency	60Hz			
Housing	Injection-Molded Thermoplastic Housing			
Testing Function	Manual Push to Test Button			
Operating Temperature	10°C to 40°C			
Listings & Compliance	UL 924, CEC Title 20, NFPA 70 & NFPA 101			
Environment	Damp Location Listed			
Warranty*	2 Year			

*All life safety equipment, including emergency lighting for path of egress must be maintained, serviced, and tested in accordance with all National Fire Protection Association (NFPA) and local codes. Failure to perform the required maintenance, service, or testing could jeopardize the safety of occupants and will void all warranties.

Evade Exit/Emergency Combination Series

Remote Head Specifications

Product SKU	Product Code	Input Voltage	Input Wattage	Lumens
95010	EV-RH-1-IND	3.6VDC	.8W	85
95011	EV-RH-2-IND	3.6VDC	1.5W	170
96012	EV-RH-1-OUT	3.6-24VDC	.8W	90
95013	EV-RH-2-OUT	3-12VDC	1.5W	180

Remote Head

EV-RH-1-IND

- Single, White, Indoor Remote Head
- Suitable for Damp Location. UL, cUL Listed



EV-RH-2-IND

- Double, White, Indoor Remote Head
- Suitable for Damp Location. UL, cUL Listed



EV-RH-1-OUT

- Single, Gray, Outdoor Remote Head
- Suitable for Wet Location. UL, cUL Listed



EV-RH-2-OUT

- Double, White, Outdoor Remote Head
- Suitable for Wet Location. UL, cUL Listed



Dimensions

