

LED Lamps

ProLED T8 Linear Type-A

- 2', 3', 4' Options
- No Re-Wiring Necessary
- Instant On - No Flicker
- 5-Year Warranty

Specifications

Product Description

The QuickConnect Type A lamp operates on most instant start and electronic ballasts, making LED lighting retrofit easier than ever.

Construction:

- Glass Lens
- 4' Metal End Cap
- 2', 3' Polycarbonate End Cap

Installation:

- Quick Plug&Play Installation
- Refer to ballast compatibility chart for Compatible ballasts
- Suitable for use in totally enclosed luminaires

Quick
CONNECT
Type A



Easy To Install



Food Equipment
Certification



50,000 Hours



Direct Ballast
Compatible



DLC Qualified

Performance

- Operates on Compatible T8 instant start, programmed start and emergency ballasts
- 120-277V
- 8W, 10W, 12W Option (2', 3', 4')
- 1250 - 2000 lumens
- L70>50,000
- 82 CRI
- Dimmable (4' only)

Certifications:

- cUL approved for Damp locations
- Conforms to requirements of NSF/ANSI standard 2 food equipment
- DLC Qualified. Refer to designlights.org for full list of qualified products.
- 5 Year Warranty



ProLED T8 Linear Type-A

Ordering Logic

Product Description

Lamp Size and Wattage	CCT	Lamp Type	Source
T824FR8 = 2' 8W T836FR10 = 3' 10W T824FR13 = 4' 12W	835 = 82 CRI, 3500K 840 = 82 CRI, 4000K 850 = 82 CRI, 5000K	DIR = Direct Replacement	LED = LED Source

Stock Guide

Watt	System Watt	Base	Product #	Product Code	Description	Voltage	CCT	CRI	Lumens	Useful Life	Pkg. Qty.	MOL	Equivalent Wattage	End Cap
8	10	G13	84068	T824FR8/835/DIR2/LED	T8 Linear QuickConnect 3500K	120-277V	3500K	82	1250	50,000	1/25	24"	17	PC
8	10	G13	84069	T824FR8/840/DIR2/LED	T8 Linear QuickConnect 4000K	120-277V	4000K	82	1250	50,000	1/25	24"	17	PC
8	10	G13	84070	T824FR8/850/DIR2/LED	T8 Linear QuickConnect 5000K	120-277V	5000K	82	1250	50,000	1/25	24"	17	PC
10	13	G13	83171	T836FR10/835/DIR/LED	T8 Linear QuickConnect 3500K	120-277V	3500K	82	1400	50,000	1/25	36"	25	PC
11	13	G13	82359	T836FR11/840/DIR3/LED	T8 Linear QuickConnect 4000K	120-277V	4000K	82	1400	50,000	1/25	36"	25	Metal
10	13	G13	83173	T836FR10/850/DIR/LED	T8 Linear QuickConnect 5000K	120-277V	5000K	82	1400	50,000	1/25	36"	25	PC
13	15	G13	83880	T8FR13/835/DIR3/LED	T8 Linear QuickConnect 3500K	120-277V	3500K	82	1800	50,000	1/25	48"	32	Metal
13	15	G13	83881	T8FR13/840/DIR3/LED	T8 Linear QuickConnect 4000K	120-277V	4000K	82	1900	50,000	1/25	48"	32	Metal
13	15	G13	83882	T8FR13/850/DIR3/LED	T8 Linear QuickConnect 5000K	120-277V	5000K	82	2000	50,000	1/25	48"	32	Metal

Dimensions

* For more detail visit installation instructions

