

ProLED Select Surface Downlight Series



The ProLED Select Surface Mount Downlight features an efficient, installer friendly design that provides a modern look in any application. These Downlights are CCT Selectable, 90 CRI and ETL listed for wet locations to make this product one of the most versatile fixtures on the market. This ProLED Select Surface Mount Downlight provides an extremely easy install for both new construction and retrofit projects

Key Benefits & Features

- Color selectable: 2700K, 3000K, 3500K, 4000K, 5000K
- Efficacy <86 lumens per watt
- Triac dimming to 10%
- 90+ color rendering
- 120VAC
- ETL listed for wet locations
- White powder coated steel housing
- Diffused polycarbonate lens provides low glare, shadow-free illumination
- Low profile housing
- Driver on-board design
- L70 lumen maintenance > 50,000 hours

Ordering Information

Series	Product Size	Wattage	CCT	Options
SDL = Surface Downlight	4 = 4 Inch 6 = 6 Inch 8 = 8 Inch	10 = 10 Watts 15 = 15 Watts 20 = 20 Watts	CS = Color Selectable 2700K/3000K/3500K/ 4000K/5000K	MS = Motion Sensor (available on 6 Inch product)

Product SKU	Product Code	Product Description
82993	SDL4-10-CS	ProLED Select Surface Downlight 4" 10W 650lm CCT Selectable
82994	SDL6-15-CS	ProLED Select Surface Downlight 6" 15W 1050lm CCT Selectable
82995	SDL8-20-CS	ProLED Select Surface Downlight 8" 20W 1500lm CCT Selectable
82996	SDL6-15-CS-MS	ProLED Select Surface Downlight 6" 15W 1050lm CCT Selectable with Motion Sensor



Scan to view spec sheets and other resources

