

ProLED GU24 A19 Omnidirectional Series







ProLED[®] GU24 Omnidirectional A-Shape Series lamps offer an economical and even more energy efficient alternative to non-dimmable compact fluorescent lamps





Omnidirectional Optical Design Provides 230° Light Distribution

UL Listed for Damp Location & Enclosed Luminaires

ENERGY STAR® Certified

Backed by a 3-Year Warranty

Applications: Home Education Hospitality Retail

Markets: Residential Commercial

Contact Your Customer Care Specialist For Pricing, Orders And Technical Support.


800.677.3334 www.halcolighting.com

ProLED. **GU24 A19 Omnidirectional Series**

Specifications

- Available in 2700K, 3000K, 4000K or 5000K CCT

- UL Listed for damp location and enclosed luminaires
- 230° degree beam angle creates uniform distribution of light
- 3-year warranty
- Rated for ICAT fixtures
- Non-Dimmable



Ordering Information

Product #: _ Type: _ Project: ____ Date: Comments: ____ _____ Initials: __

Savings Comparison



^v Maintenance costs based on 15 minutes at \$40 per/hr ¥ Energy costs based on \$0.11 kWh



0	Watt	Base	Product #	Product Code	Voltage	Color Temp	CRI	Lumens	Useful Life	Beam Angle	Pkg Qty	MOL	Equivalent Wattage	Certification
	9.5W	GU24	83180	A19FR9/827/OMNI2/GU24/LED	120	2700K	82	800	15,000	220°	1/6	4.33"	60W	UL, ES
	9.5W	GU24	83181	A19FR9/830/OMNI2/GU24/LED	120	3000K	82	800	15,000	220°	1/6	4.33"	60W	UL, ES
	9.5W	GU24	83182	A19FR9/840/OMNI2/GU24/LED	120	4000K	82	800	15,000	220°	1/6	4.33"	60W	UL, ES
	9W	GU24	88058	A19FR9-850-GU24-LED	120	5000K	80	800	15,000	220°	1/48	4.17"	60W	ETL, ES
	11.5W	GU24	83184	A19FR11/827/OMNI2/GU24/LED	120	2700K	82	1100	15,000	220°	1/6	4.33"	75W	UL, ES
	15W	GU24	88060	A19FR15-840-GU24-LED	120	4000K	80	1600	15,000	220°	1/48	4.64"	100W	ETL, ES

• NEW ITEM! * Useful Life is defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to burn past this point, but at decreased light levels.

Marranty – Commercial / Industrial: This product is warranted for 3 years from the date of purchase. 15,000 hour useful life rating is based on a maximum ambient temperature of 45°C. Exceeding this ambient temperature rating may result in reduced life.

Halco Lighting Technologies 2940 Pacific Drive I Norcross, GA 30071 I Toll Free 800.677.3334 I Phone 770.242.3612 I Fax 800.880.0822 I halcolighting.com I Atlanta I Chicago I Cleveland I Houston I Los Angeles I Phoenix

© 2021 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change. 080421. Re-order #9117