

ProLED. GU24 A19 Omnidirectional Series







ProLED® GU24 Omnidirectional A-Shape Series lamps offer an economical and even more energy efficient alternative to non-dimmable compact fluorescent lamps



Omnidirectional Optical Design Provides 220° Light Distribution

UL Listed for Damp Location& Enclosed Luminaires

ENERGY STAR® Certified

Backed by a 3-Year Warranty

Applications:

Home Education Hospitality Retail

Markets:

Residential Commercial




Contact Your Customer Care Specialist For Pricing, Orders And Technical Support.

ProLED_® **GU24 A19 Omnidirectional Series**


Product #:	Type:
Project:	Date:
Comments:	Initials:

Specifications

- Available in 2700K, 3000K, 4000K or 5000K CCT
- UL Listed for damp location and enclosed luminaires
- 220° degree beam angle creates uniform distribution of light
- 3-year warranty
- Rated for ICAT fixtures
- Non-Dimmable



Savings Comparison



- v Maintenance costs based on 15 minutes at \$40 per/hr
- ¥ Energy costs based on \$0.11 kWh







Ordering Information

0	Watt	Base	Product #	Product Code	Voltage	Color Temp	CRI	Lumens	Useful Life	Beam Angle	Pkg Qty	MOL	Equivalent Wattage	Certification
	9W	GU24	88056	A19FR9-827-GU24-LED	120	2700K	80	800	15,000	220°	1/48	4.17"	60W	ETL, ES
	9W	GU24	88056	A19FR9-830-GU24-LED	120	3000K	80	800	15,000	220°	1/48	4.17"	60W	ETL, ES
	9W	GU24	88057	A19FR9-840-GU24-LED	120	4000K	80	800	15,000	220°	1/48	4.17"	60W	ETL, ES
	9W	GU24	88058	A19FR9-850-GU24-LED	120	5000K	80	800	15,000	220°	1/48	4.17"	60W	ETL, ES
	11W	GU24	88059	A19FR11-827-GU24-LED	120	2700K	80	1100	15,000	220°	1/48	4.64"	75W	ETL, ES
	15W	GU24	88060	A19FR15-840-GU24-LED	120	4000K	80	1600	15,000	220°	1/48	4.64"	100W	ETL, ES

© NEW ITEM!

*Useful Life is defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to burn past this point, but at decreased light levels.

Warranty — Commercial / Industrial: This product is warranted for 3 years from the date of purchase.

15,000 hour useful life rating is based on a maximum ambient temperature of 45°C. Exceeding this ambient temperature rating may result in reduced life.